



AMP-TWIST SL-Series Modular Jack, category 6, shielded, 4 pair, for FTP cables, rear exit, without dust cover

OBSOLETE

This product was discontinued on: December 19, 2018

Replaced By

- 2153448-4 AMP-TWIST SLX, 6S,GY AMP-TWIST SLX Series Modular Jack, category 6, shielded , 4 Pair, without dust cover, gray
- 760238140 USL600-SHLD, GY Uniprise SLX Series Modular Jack, category 6, shielded , 4 Pair, without dust cover, gray

Product Classification

Portfolio	NETCONNECT®
Product Series	SL Series
Product Type	Modular jack
Regional Availability	Australia/New Zealand EMEA Latin America

Dimensions

Compatible Cable Diameter, maximum	9.00 mm 0.35 in
Compatible Insulated Conductor Diameter, maximum	1.600 mm 0.063 in
Depth	36.70 mm 1.44 in
Height	20.50 mm 0.81 in
Width	15.30 mm 0.60 in

Electrical Specifications

ANSI/TIA Category	6
Current Rating, maximum	0.75 A
Safety Voltage Rating	150 Vac
Transmission Standard	ANSI/TIA-568-C.2 IEEE 802.3an IEEE 802.3at ISO/IEC 11801 Class E

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)

General Specifications

Cable Type	Shielded
Color	Silver
Package Quantity	12
Packaging Type	Tray in box
Panel Cutout, recommended	14.78 x 20.07 mm (0.58 x 0.79 in)
Panel Thickness, recommended	1.60 mm

Mechanical Specifications

Conductor Gauge, solid	26–22 AWG
Conductor Gauge, stranded	26–24 AWG
Conductor Type	Solid Stranded
Contact Base Material	Beryllium copper
Contact Plating Material	Gold
Contact Plating Thickness	1.27 µm
Material Type	Zinc alloy
Outlet Type	Standard
Plug Insertion Life, minimum	750 times
Plug Retention Force, minimum	30 N 7 lbf
Termination Tool	SL Termination tool
Termination Type	IDC
Wiring	T568A T568B

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant

