NPC6ASVDB-BL



NPC RJ45 Patch Cord, category 6A, Shielded, CM (PVC), Blue

- High-performance patch cords exceeding industry standards supporting NETCONNECT channel specifications
- Standardized transparent, slim-line boots provides consistent patch cord appearance and supports highest density applications
- Colored clips are available to fit the transparent boot, eliminating the need of multiple colors for matching every jacket color
- Colored pull latch tabs are available for easier plug release handling from the modular jack

Product Classification

Portfolio NETCONNECT®

Product Series NPC

Product Type Twisted pair patch cord

Regional Availability Latin America

Construction Materials

Insulation Material Polyethylene

Dimensions

Cord Length, maximum 100 ft | 999 in Cord Length, minimum 1 ft | 6 in

Diameter Over Jacket 5.70 mm | 0.22 in

Electrical Specifications

ANSI/TIA Category 6A

Environmental Specifications

Environmental Space Non-plenum

Flammability Rating CM

Operating Temperature -20 °C to +60 °C (-4 °F to +140 °F)

Relative Humidity Up to 93%, non-condensing

Safety Standard UL 1863

General Specifications

Cable Type S/FTP (shielded)

Interface, connector A RJ45 plug
Interface, connector B RJ45 plug
Jacket Color Blue

page 1 of 2 September 12, 2019



NPC6ASVDB-BL

Interface Feature, connector A Standard Interface Feature, connector B Standard

Package Quantity 1
Pairs, quantity 4

Mechanical Specifications

Conductor TypeStrandedConductor Gauge, stranded26 AWGMaterial TypePVCPlug Insertion Life, minimum750 timesWiringT568B

Regulatory Compliance/Certifications

AgencyClassificationRoHS 2011/65/EUCompliant



Included Products

6-2111989-3 | MP-6S-C-1 — Modular Plug Kit, category 6, shielded, 8-position, 5.7 – 7.0 mm max cable jack OD, 100/bag

2843032-3 | MP-Boot-S/SL-AB — Modular Plug Shielded Slim-Line Boot for Category 6A/6 and Category 5e EMT Plugs, 4.7 to 6.0 mm, transparent

